ELTSM-4



SPECIFICATIONS

RATING: 50mA, 12VDC
ELECTRICAL LIFE: 30,000~50,000 cycles
CONTACT RESISTANCE: 500mΩ max
INSULATION RESISTANCE: 100MΩ min. 100VDC
DIELECTRIC STRENGTH: 250VAC/1 min
OPERATION FORCE: 260 ± 70g
160 ± 50g
STORAGE TEMPERATURE: -30°C to +80°C
CONTACT ARRANGEMENT: 1 pole 1 throw

DIMENSION



Model No.	H
ELTSM-41	3.8
ELTSM-433	7.0

Circuit Diagram







P.C.B Layout



ELTSK-5









Circuit Diagram



P.C.B Layout



HOW TO ORDER

ELTS □ — □ □ □ — □ — □

M = Surface Mounting Type
K = Slim type

Prod Size: 4 = 4.5 x 4.5
5 = 5.2 x 5.2

Dimension H:

Code	ELTSM-4	ELTSK-5
1	3.8	0.8
2		1.5
33	7.0	

Operation Force:
N = 160g
R = 260g

Package Style:
T/R: Tape & Reel

RoHS code
H= RoHS Compliant

The dimensions in the catalogue and website are for reference only, not suitable for formal acknowledge.