



**SPECIFICATION**

Contact Rating	50mA, 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	250V AC/1 minute
Travel	0.20 mm
Operating Temp.	-25°C ~ +70°C
Storage Temp.	-30°C ~ +80°C

PAPT NO	TS-1145-X-X
Operating Force	A: 100gf B: 160gf C: 260gf
Height	H: 2.5
Keystake	A: PA46 B: Silica gel

CIRCUIT DIAGRAM

P.C.B MOUNTING HOLES

PACKING

REEL TYPE

3,000/1 REEL (EA)

# SWITCH CONNECTOR

⑤	Terminal	—	4	Brass (0.30t)	ag Plated	—
④	Contact	—	1	F.ag/SUS	—	—
③	Base	—	1	LCP	—	—
②	Cover	—	1	Brass	Tin plated	—
①	Keystake	—	1	PA46/Silica gel	—	—
ITEM	PAPT NAME	TER.NO	QTY	MATERIAL	FINISHING	REMARK

						DSND		DATE		SCALE: N/A	MODEL TYPE: <b>TACT SWITCH</b>		
						DWN		DATE		VIEW:	PART NO.:		
						CHKD		DATE		UNIT: mm	DWG NO.:		
						APPD		DATE		SIZE: A4	<b>TS-1145-X-A</b>		
						XKB INDUSTRIAL PRECISION CO.,LIMITED					WEIGHT	SHEET	REVISION
											1.0g	1/1	A0