


SPECIFICATIONS

- 1.Operating temperature range: -30°C to 85°C
- 2.Rating: DC12V 50mA
- 3.Insulation resistance: $100\text{M}\Omega$ min 100V DC
- 4.Dielectric strength: 250V AC for 1min.
- 5.Contact resistance: $100\text{m}\Omega$ Max
- 6.Operating force: $250\pm 50\text{gf}$
- 7.Travel: $0.15\pm 0.05\text{mm}$
- 8.Operating life: 250gf 100,000 Cycle

PAPT NO	TS-1809SM-X
Operating Force	A:100gf B:160gf C:260gf

							DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH		
					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.: TS-1809SM		
△X					L ≤ 4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.: TS-1809SM-X		
△X					4 < L ≤ 16	±0.3								
△X					16 < L ≤ 63	±0.4								
MARK	DESCRIPTION			DATE	REVISED	APPROVED	APPD		DATE		SIZE: A4			
REVISIONS						UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT	SHEET	REVISION
www.xk-dg.cn www.1k0k.com www.1k0k.cn												1.0g	1/1	A0

△X					ANGLAR	±5°
△X					$L \leq 4$	±0.2
△X					$4 < L \leq 16$	±0.3
MARK	DESCRIPTION	DATE	REVISED	APPROVED	$16 < L \leq 63$	±0.4
					$L > 63$	±0.5

REVISIONS

www.xk-dg.cn www.1k0k.com www.1k0k.cn

UNSPECIFIED TOLERANCES

XKB INDUSTRIAL PRECISION CO.,LIMITED