


SPECIFICATION

Contact Rating	50mA, 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	250V AC/1 minute
Travel	0.25 mm
Operating Temp.	-25°C ~ +70°C
Storage Temp.	-30°C ~ +80°C

PAPT NO	TS-1109TP-X
Operating Force	A: 100gf B: 160gf C: 260gf
Height	H: 3.15

⑤	Terminal	—	2	Brass (0.30t)	ag Plated	—
④	Contact	—	1	F.ag/SUS		—
③	Base	—	1	PA46	Natural	—
②	Cover	—	1	Brass	Tin plated	—
①	Keystake	—	1	PA46		—
ITEM	PAPT NAME	TER.NO	QTY	MATERIAL	FINISHING	REMARK

						DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH			
					units: mm	DWN		DATE		VIEW: 	PART NO.:			
△X						CHKD		DATE		UNIT: mm	DWG NO.:			
△X					X.X ±0.2mm	APPD		DATE		SIZE: A4	TS-1109TP-X			
△X					X.XX ±0.1mm	XKB INDUSTRIAL PRECISION CO.,LIMITED						WEIGHT	SHEET	REVISION
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX ±0.05mm							1.0g	1/1	A0
REVISIONS					UNSPECIFIED TOLERANCES									
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn														