


SPECIFICATION

Contact Rating	50mA, 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	250V AC/1 minute
Travel	0.25 mm
Operating Temp.	-25°C ~ +70°C
Storage Temp.	-30°C ~ +80°C

PAPT NO	TS-1102T-X
Operating Force	A: 100gf B: 160gf C: 260gf
Height	D: 7.3

							DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH		
					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.: TS-1102T		
△X					L ≤ 4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.: TS-1102T-X		
△X					4<L ≤ 16	±0.3	APPD		DATE		SIZE: A4			
△X					16<L ≤ 63	±0.4								
MARK	DESCRIPTION		DATE	REVISED	APPROVED	L > 63	±0.5							
REVISIONS						UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT	SHEET	REVISION
www.xk-dg.cn www.1k0k.com www.1k0k.cn												1.0g	1/1	A0