


### SPECIFICATION

Contact Rating	50mA, 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	250V AC/1 minute
Travel	0.25mm
Operating Temp.	-25°C ~ +70°C
Storage Temp.	-30°C ~ +80°C

PAPT NO	TS-CB1157-X-X
Operating Force	A:100gf B:160gf C:260gf
Height	H:A:3.8 B:4.3

⑤	Terminal	—	5	Brass (0.30t)	ag Plated	—
④	Contact	—	1	F.ag/SUS		—
③	Base	—	1	PA46	Natural	—
②	Cover	—	1	Brass	Tin plated	—
①	Keystake	—	1	PA46		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

						DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH		
					units: mm	DWN		DATE		VIEW: 	PART NO.:		
△X					tolerance:			DATE		UNIT: mm	DWG NO.:		
△X					X.X ±0.2mm	CHKD		DATE			TS-CB1157-X-X		
△X					X.XX ±0.1mm								
MARK	DESCRIPTION			DATE	REVISED	APPROVED	X.XXX ±0.05mm	APPD	DATE	SIZE: A4			
REVISIONS						UNSPECIFIED TOLERANCES					XKB INDUSTRIAL PRECISION CO.,LIMITED		
www.xk-da.cn   www.helloxkb.com   www.helloxkb.cn											WEIGHT 1.0g	SHEET 1/1	REVISION A0