





Code-X	H
A	4.3
B	4.5
C	5.0
D	5.5
E	6.0
F	6.5
G	7.0
H	7.5
I	8.0

SPECIFICATION

Contact Rating	50mA, 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	250V AC/1 minute
Travel	0.25mm
Operating Temp.	-25°C +70°C
Storage Temp.	-30°C +80°C

PAPT NO	TS-1102US-X-X
Operating Force	B:160gf C:260gf
Height	Code-X



⑤	Terminal	——	2	Brass（0.30t）	ag Plated	————
④	Contact	——	1	F.ag/SUS		————
③	Base	——	1	PA46	Natural	————
②	Cover	——	1	Brass	Tin plated	————
①	Keystake	——	1	PA46		————
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

				units:	mm
△X				tolerance:	
△X				X.X	±0.2mm
△X				X.XX	±0.1mm
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX ±0.05mm
REVISIONS					UNSPECIFIED TOLERANCES

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm	
APPD		DATE		SIZE: A4	DWG NO.: TS-1102US-X-X

XKB INDUSTRIAL PRECISION CO.,LIMITED

WEIGHT	SHEET	REVISION
1.0g	1/1	A0

XKB SWITCH CONNECTOR