


SPECIFICATION

Contact Rating	50mA 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	250V AC/1 minute
Travel	0.25 mm
Operating Temp.	-25°C ~ +70°C
Storage Temp.	-30°C ~ +80°C

PAPT NO	TC-111A-X
Operating Force	A: 130gf B: 200gf C: 300gf D: 500gf
Height	H: 6.65

It is suggested to use a P.C.board of 1.6mm thick

⑤	Terminal	—	2	Brass (0.30t)	ag Plated	—
④	Contact	—	1	F.ag/SUS		—
③	Base	—	1	PA66	Natural	—
②	Cover	—	1	Brass	Tin plated	—
①	Keystake	—	1	Steel ball		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

						DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH			
					units: mm	DWN		DATE		VIEW: 	PART NO.:			
△X					tolerance:									
△X					X.X	±0.2mm	CHKD		DATE		UNIT: mm			
△X					X.XX	±0.1mm						DWG NO.:		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX	±0.05mm	APPD		DATE		SIZE: A4	TC-111A-X		
REVISIONS					UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED					WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn												1.0g	1/1	A0