



FEATURES

- Light operating force.
- Long term low contact resistance.
- Momentary or latching operation.
- Short stroke 1.5mm to latch.
- Compact spacing on PCB of 8.0mm.

SPECIFICATIONS

1.ELECTRICAL

● Contact rating	0.1A, 30VDC
● Contact resistance	50mWMax.
● Insulation resistance	100MWMin. at 250VDC
● Dielectric strength	250VAC Min. for 60 sec.

2.MECHANICAL AND ENVIRONMENTAL

● Temperature rating	Operating: -15℃ to +55℃ Storage: -25℃ to +65℃
● Operation force	160±80gf
● Stroke	Lock Stroke: 1.5±0.2mm Full Stroke: 2.5±0.2mm
● Operating life	full load: 1x10 ⁴ cycles no load: 1x10 ⁵ cycles
● Contact form	DPDT

PAPT NO	XKB8080-X
OPERATION	W:NO LOCK Z:LOCK

⑦	Contact	2	Phosphor bronze	ag Plated	_____
⑥	Terminal	6	Brass strip	ag Plated	_____
⑤	spring	1	SUS	Natural	_____
④	Base	1	POM		_____
③	Crochet Needle	1	SUS	Natural	_____
②	Cover	1	POM		_____
①	Keystake	1	POM		_____

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
					ANGLAR	±5°
					L≤4	±0.2
					4<L≤16	±0.3
					16<L≤63	±0.4
					L>63	±0.5
					UNSPECIFIED TOLERANCES	

DSND		DATE		SCALE: N/A	MODEL TYPE:
DWN		DATE		VIEW:	PUSH SWITCH
CHKD		DATE		UNIT: mm	PART NO.: XKB8080
APPD		DATE		SIZE: A4	DWG NO.: XKB8080-X
XKB INDUSTRIAL PRECISION CO.,LIMITED					WEIGHT 1.0g
					SHEET 1/1
					REVISION A0

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
△X					
△X					
△X					
REVISIONS					
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn					