


NOTE:
 Rating: DC 12V 50mA
 Operating Force: 200±100gf
 Lifetime: 100,000 Cycles

PAPT NO	L
SK-3278S-L1	2.0
SK-3278S-L2	3.0
SK-3278S-L3	4.0

ITEM	PAPT NAME	TER. NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	12	Brass (0.30t)	ag Plated	—
④	Contact spring	—	1	Beryllium copper	—	—
③	Base	—	1	LCP	—	—
②	Cover	—	1	SUS	Tin plated	—
①	Keystake	—	1	PA46	—	—

							DSND		DATE		SCALE: N/A	MODEL TYPE: SLIDE SWITCH	
					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.:	
△X					L ≤ 4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.: SK-3278S-X	
△X					4<L ≤ 16	±0.3	APPD		DATE		SIZE: A4		
△X					16<L ≤ 63	±0.4							
MARK	DESCRIPTION			DATE	REVISED	APPROVED	L > 63	±0.5					
REVISIONS							UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn											WEIGHT 1.0g	SHEET 1/1	REVISION A0