
















MODEL CODE

SS-23E32 -

L (mm)
~

Knob Type			
GAA		GDI	
GAB		ATA	
GAC		NTA	
GAD		NTH	
GAE		MXA	
GBR		MXH	
GDB		NYA	

RATING	0.3A 50V DC
CIRCUIT	1P2T
CONTACT RESISTANCE	100mΩ MAX.
TRAVEL	2mm
OPERATING FORCE	250±100gf
OPERATING LIFE(cycles)	10,000

							DSND		DATE		SCALE: N/A	MODEL TYPE: SLIDE SWITCH		
ΔX					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.:		
ΔX					L ≤ 4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.: SS-22F32		
ΔX					4<L ≤ 16	±0.3								
MARK	DESCRIPTION	DATE	REVISED	APPROVED	16<L ≤ 63	±0.4	APPD		DATE		SIZE: A4	WEIGHT 1.0g SHEET 1/1 REVISION A0		
					L > 63	±0.5								
REVISIONS					UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED							
www.xk-dg.cn www.1k0k.com www.1k0k.cn														