



NOTE:
Rating: DC 12V 50mA
Operating Force:200±100gf
Lifetime:100,000 Cycles

PAPT NO	L
SS-3390S-L0	1.0
SS-3390S-L1	1.5
SS-3390S-L2	2.0
SS-3390S-L3	3.0

ITEM	PAPT NAME	TER. NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	6	Brass (0.30t)	ag Plated	—
④	Contact spring	—	1	Beryllium copper	—	—
③	Base	—	1	LCP	—	—
②	Cover	—	1	SUS	Tin plated	—
①	Keystake	—	1	PA46	—	—

					ANGLAR	±5°	DSND		DATE		SCALE: N/A	MODEL TYPE:
△X					L ≤ 4	±0.2	DWN		DATE		VIEW:	SLIDE SWITCH
△X					4 < L ≤ 16	±0.3	CHKD		DATE		UNIT: mm	PART NO.:
△X					16 < L ≤ 63	±0.4	APPD		DATE		SIZE: A4	DWG NO.:
MARK	DESCRIPTION	DATE	REVISED	APPROVED	L > 63	±0.5						SS-3390S-X
REVISIONS					UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn										1.0g	1/1	A0