









SWITCH CONNECTOR

NOTE:
1.Rating : DC 5V 10mA
2. Contact Resistance: 100mΩMAX
3. Insulation Resistance: 100MΩMIN
4. Soldering Temper: 260±5°/5s
5. Mechanical Life: 100,000 cycles
6. Ever Portion 80 ± 50 gf
7. Push Portion 205 ± 80 gf
8. Travel: −24° 0° +24°

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑤	Spring	——	1	SUS	Natural	——
④	Terminal	——	5	Phosphor Bronze	Plating silver	——
③	Cover	——	1	SUS	Natural	——
②	Base	——	1	LCP	Black	——
①	Keystoke	——	1	PPA	Black	——

MARK	DESCRIPTION	DATE	REVISED	APPROVED
△X				
△X				
△X				

REVISIONS

UNSPECIFIED TOLERANCES	
ANGLAR	±5°
L≤4	±0.2
4<L≤16	±0.3
16<L≤63	±0.4
L>63	±0.5

DSND		DATE		SCALE: N/A	MODEL TYPE: MULTIFUNCTIONAL SWITCHS
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm	DWG NO.: TM-2011
APPD		DATE		SIZE: A4	

XKB INDUSTRIAL PRECISION CO.,LIMITED

WEIGHT	SHEET	REVISION
1.0g	1/1	A0