

- Typical Specifications :
1. Rating : DC 12V 50mA
 2. Insulation resistance: $\geq 100M\Omega$
 3. Withstand voltage: AC 500V/1min
 4. Life: 100,000 Cycles Min.



Circuit Diagram


NO.1	
PART NO	H
D	3.5
F	5

NO.2	
PART NO	vigor
3	180±30
4	250±30
5	350±50

NO.3-NO.4	
PART NO	NOTE
01~99	SERIAL NUMBER

⑤	Terminal	—	4	Phosphor Bronze	Plating silver	—
④	Contact	—	1	F.Ag/SUS	—	—
③	Base	—	1	PA46	Black	—
②	Cover	—	1	SPCC	Plating Sn	—
①	Keystoke	—	1	Silica gel	White	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	HILIOE ELECTRONICS CO.,LTD		
DRAWN	xu qi feng	2014.10.28			

		修改按材质为蓝色硅胶20180407				TITLE: TACT SWITCHES	
		修改型号为单弹20160927				PART NO. K2-1156UP-□□□□W-□□	
B	—	NEW				SCALE: 1:1	
A	—	DESCRIPTION.				PROJ. 	
REV.	DATE.	CHANGE.	CHECK.	APPRO.	SHEET 1 OF 1		
TOLERANCES ARE							
30~以上							
10~30							
5~10							
~ 5							
±0.30							
±0.20							
±0.15							
±2°							
DRAWING NO.							