



| | | | | | | | |
|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| L=1.2 | PJ-393B-A | PJ-393B-B | PJ-393B-C | PJ-393B-D | PJ-393B-E | PJ-393B-F | PJ-393B-G |
| L=1.4 | PJ-393B-H | PJ-393B-I | PJ-393B-J | PJ-393B-K | PJ-393B-L | PJ-393B-M | PJ-393B-N |
| L=0.8 | PJ-393B-O | PJ-393B-P | PJ-393B-Q | PJ-393B-R | PJ-393B-S | PJ-393B-T | PJ-393B-U |
| Schematic | | | | | | | |

Rating:0.5A 30V DC
Contact Resistance:100 mΩ Max.
Operating temperature:-20℃~70℃
Operating force:3-20N
Operating Life:5,000cycles

| | | | | | | |
|----------------|-----------|------------|---------------------|-----------------|-------------|--------------|
| ② | Terminal | — | 8 | Phosphor bronze | Au Plating | — |
| ① | Housing | — | 1 | Nylon | Black | — |
| ITEM | PART NAME | TER.NO. | QTY. | MATERIAL | FINISHING | REMARK |
| APPROVALS | | DATE | ELECTRONICS CO.,LTD | | | |
| DRAWN | J.X.Zhong | 2013/11/11 | PHONE JACKS | | | |
| CHECKED | | | PJ-393B | | | |
| APPROVALS | | | PROJ-1 OF 1 | | | |
| TOLERANCES ARE | | 30~0.15 | ±0.30 | ANGLE | UNIT: mm | SCALE: 1:1 |
| | | 10~0.30 | ±0.20 | | | |
| | | 5~10 | ±0.15 | ±2° | DRAWING NO. | SHEET 1 OF 1 |
| ECN NO. | REV. | DATE. | DESCRIPTION. | | | |
| | A | | NEW | | | |
| | | | CHECK. | | | |
| | | | APPRO. | | | |