


此处打胶防水

- Specifications**
1. Rating : DC 30V 0.5A
 2. Dielectric withstanding: 100V(AC) for 1min
 3. Contact Resistance : 50mΩMax
 4. Insulation Resistance: 100MΩ Min
 5. Operating Temperature Range: -25℃+80℃
 6. Operating Force : 8-30N
 7. Operating Life : 5,000Cycles

| ITEM | PART NAME | TER. NO. | QTY. | MATERIAL | FINISHING | REMARK |
|------|-----------|----------|------|--------------|-----------|--------|
| ③ | Snell | — | 1 | SUS | Natural | — |
| ② | Contact | — | 5 | Copper Alloy | Au Plated | — |
| ① | Housing | — | 1 | LCP | Black | — |

| | | | |
|-----------|---------|-----------|---|
| APPROVALS | | DATE |  ELECTRONICS CO., LTD |
| DRAWN | JKUN.LU | 2014/9/29 | |

| | | | | | | |
|---------|------|-------|---|--------------|------------|-----------------|
| | | | CHECKED | | TITLE: | 防水USB CONNECTOR |
| B | — | | APPROVALS | | PART NO. | U-E-M5SS-Y-1 |
| A | — | NEW | | | | |
| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
| | | | TOLERANCES ARE | | | |
| | | | 30~12.7 ±0.30 10~3.0 ±0.20 5~1.0 ±0.15 | ANGLE ±2° | UNIT: mm | SCALE: 1:1 |
| | | | DRAWING NO. | | SHEET 1 OF | |