



MRK.	DATE	REVISION	SIGN
△			

# Specification

1. Rating : 25mA, 12V DC (Switching)  
25mA, 24V DC (None-Switching)
2. Contact Resistance : 100mΩ Max
3. Insulation Resistance : 100MΩ Min
4. Operating Force : 700gf Max
5. Life cycle : 10,000 steps

		Real Code				
16 P o s i t i o n		C	1	2	4	8
	0	●				
	1	●	●			
	2	●		●		
	3	●	●	●		
	4	●			●	
	5	●	●		●	
	6	●		●	●	
	7	●	●	●	●	
	8	●				●
	9	●	●			●
	A	●		●		●
	B	●	●	●		●
	C	●			●	●
	D	●	●		●	●
	E	●		●	●	●
	F	●	●	●	●	●

## STANDARD LAYOUT

01	H Series			재질 <지정안함>		1		-	
NO.	DESCRIPTION			MATERIAL		COLOR/FINISH		Q.TY	VENDOR
DRAW/DESIGNED	CHECKED		APPROVED		G.TOL	TITLE	H Series		
					±0.1	MODEL	HAER-16S		
2018-07-09				UNIT mm	SCALE 3:1	SHEET			
SUNGmun ELECTRONICS CO.,LTD					SIZE	DRAW NO.	HAER-16S0-01		1/1
					A4				

